



PRODUCT DATA SHEET

MECHANICAL & PHYSICAL PROPERTIES

FD 90

TYPE	Three Layer particleboard with high performance Confirm to BS EN 312
COMPOSITION:	100% of selected recycled softwood , hard wood , Vermiculite , resin , sawmill residues ,carpenters residues
FIRE PERFORMANCE STANDARD:	BS 467 Part 22
ASSESSMENT REPORT:	PAR 01 / 11018 Rev B / Chilt / A12069Rev C
FIRE BEHAVIOR CATEGORY:	Resist Fire for 90 Minutes
CERTIFICATION:	IFC - FRTD483 & BM TRADA - 589
GREEN PRODUCT:	FSC – TT-COC-004433
ENVIRONMENT FOOT PRINT:	100% Recycled product
DENSITY:	600 Kg /m10± ³
MOISTURE CONTENT:	08-10 ±2
BOARD THICKNESS:	64mm ±0.3
BOARD SIZE:	935 X 2135 X 64 mm , 1220 x 2440 x 64 mm
BOARD SURFACE:	-----
EMISSION CLASSIFICATION:	E 1 according to EN 120 Content < 8mg /100g
ACOUSTIC PERFORMANCE:	Has potential to provide RW 34 dB when used with suitable seal

+971 4 884 7758

+971 4 884 7759

P.O.Box 263127

info@fireban.net

www.fireban.net